


WinterStraw™

SNG

Single Net Green ~ 100 yd² ~ 8' Wide x 112.5' Long



Winters Excelsior
Company

Straw Erosion Control Blanket

Installation Instructions - General Slope

1. Always prepare the soil before installation of blankets and apply seed and fertilizer to match your soil conditions.
2. Dig a 6" x 6" trench 3 feet back from the top of your slope and anchor the blanket inside using staples. Backfill the trench and compact the soil before rolling out the blanket.
3. Roll out the blanket either vertically down the slope or horizontally across the slope.
4. Staple blankets according to site conditions and the included staple pattern guide.
5. Use a minimum of 2" when overlapping blankets running parallel each other. Secure the seam using staples.
6. Shingle blankets using a 4" minimum overlap when splicing blankets on a downhill slope. The up-hill blanket should always overlap the downhill blanket.
7. Roll the blanket at least two feet past the bottom of the slope and secure using staples every 12" on center.

Additional Instructions - Channel Application

1. Roll the first blanket in the bottom of the channel in the direction of water flow.
2. Install additional blankets parallel the first blanket and away from the center of the channel. Use a minimum of 6" shingle overlap and secure using 2 staggered rows of staples on 4' centers.
3. Blankets on the top of the slope must be secured with staples in a 6" x 6" trench.
4. For additional support in the channel install a check slot across the channel every 25 feet and at the terminal end of the channel.
5. Never place a seam in the bottom or center of the channel

NOTE: These instructions are meant to be a general guideline for installation and cannot take into account project specific issues. Please consult our website or call regarding further detailed instruction options.

