


2CB-4

2CB-4-TR

WBSF2-CB-4 G




## SIDE VIEW

USE STEEL POSTS THAT MEET THE STATE STANDARDS AND SPECIFICATION FOR THE STATE THAT THE SILT FENCE WILL BE INSTALLED.


POST SPACING MAY VARY BY STATE DEPENDING ON THE STATE MAX O.C. SPECIFICATION.

USE WOVEN-IN BELTS AS ATTACHMENT POINTS FOR THE TIES.




MINIMUM OF 8" BLACK UV 120 LBS. ZIP TIES FOR STEEL  
1" X 1 1/4" STAPLES FOR WOOD

TO BE PLACED AT EACH SUPPORT BELT.  
(4 BELTS TOTAL) BOTTOM STAPLE OR WIRE TIE IS AT GROUND LEVEL.




USE OAK/HARDWOOD POST  
MINIMUM 1 1/4" x 1 3/4" x 48"



## FRONT ELEVATION

### REPAIR DETAIL

ATTACHING TWO SILT FENCES WHEN TRENCHING IS USED



## PLAN VIEW

# HEAVY DUTY WOVEN BELTED WBSF2 CB-4 SILT FENCE 2 STAGE COMBO

FRAME MATERIAL: OAK/HARDWOOD OR STEEL

FILTER FABRIC MATERIAL: REFER TO SPEC

SCALE: NOT TO SCALE

LAST UPDATED: 04-27-2020 G